


1.6 Balken – UNP

Profiel	Afmeting in mm						M ² verf oppervl. p/m	Gewicht in kg p/m	
	h	x	b	x	d	x			t
80	80	x	45	x	6,0	x	8,0	0,312	8,90
100	100	x	50	x	6,0	x	8,5	0,372	10,80
120	120	x	55	x	7,0	x	9,0	0,434	13,70
140	140	x	60	x	7,0	x	10,0	0,489	16,40
160	160	x	65	x	7,5	x	10,5	0,546	19,20
180	180	x	70	x	8,0	x	11,0	0,611	22,50
200	200	x	75	x	8,5	x	11,5	0,661	25,80
220	220	x	80	x	9,0	x	12,5	0,718	30,00
240	240	x	85	x	9,5	x	13,0	0,775	33,90
260	260	x	90	x	10,0	x	14,0	0,834	38,70
280	280	x	95	x	10,0	x	15,0	0,890	42,60
300	300	x	100	x	10,0	x	16,0	0,950	47,10
320	320	x	100	x	14,0	x	17,5	0,982	60,70
350	350	x	100	x	14,0	x	16,0	1,047	61,80
380	380	x	102	x	13,5	x	16,0	1,110	64,40
400	400	x	110	x	14,0	x	18,0	1,182	73,20



Balkstaal UNP

Kwaliteit
 S235JRG2 volgens EN 10025.

Lengte
 Uit voorraad leverbaar tot 24 meter.

