


## 4.1 Rondstaal

Afmeting in mm	Gewicht in kg p/m	Zink	Afmeting in mm	Gewicht in kg p/m	Zink
		Gewicht in kg p/m			Gewicht in kg p/m
6	0,23	0,24	45	12,74	13,38
8	0,41	0,43	48	14,22	14,79
10	0,63	0,66	50	15,69	16,47
12	0,91	0,96	55	19,10	20,01
13	1,06	1,11	60	22,62	23,75
14	1,23	1,29	65	26,49	27,81
15	1,39	1,46	70	30,77	32,31
16	1,61	1,69	75	35,40	37,17
18	2,04	2,13	80	40,25	42,26
19	2,27	2,38	85	45,40	47,22
20	2,52	2,64	90	50,85	53,39
22	3,04	3,19	95	56,70	58,97
24	3,62	3,80	100	62,90	66,05
25	3,92	4,12	110	76,00	79,80
28	4,92	5,17	120	90,50	95,03
30	5,66	5,94	130	106,00	111,30
32	6,43	6,75	140	123,00	129,15
35	7,69	8,07	150	142,00	149,10
36	8,15	8,56	160	157,80	165,69
38	9,07	9,43	170	181,00	190,05
40	10,05	10,55	180	199,80	209,79
42	11,10	11,66	200	252,00	264,60



### Rondstaal

Kwaliteit  
S235JRG2 volgens EN 10025.

Lengte  
Uit voorraad leverbaar op 6 meter.

## 4.2 Vierkantstaal

Afmeting in mm	Gewicht in kg p/m	Zink	Afmeting in mm	Gewicht in kg p/m	Zink
		Gewicht in kg p/m			Gewicht in kg p/m
6	0,29	0,30	35	9,80	10,19
8	0,51	0,54	40	12,84	13,48
10	0,80	0,84	45	16,20	16,85
12	1,15	1,21	50	19,97	20,97
14	1,57	1,65	55	24,20	25,17
15	1,80	1,89	60	28,84	30,28
16	2,05	2,15	65	33,80	35,15
18	2,88	3,02	70	39,23	41,19
20	3,20	3,36	75	45,00	46,80
22	3,87	4,06	80	51,15	53,71
25	5,00	5,25	90	64,80	68,04
30	7,21	7,57	100	80,00	84,00
32	8,19	8,52	120	115,0	119,6



### Vierkantstaal

Kwaliteit  
S235JRG2 volgens EN 10025.

Lengte  
Uit voorraad leverbaar op 6 meter.

